

**Karta Techniczna Wyrobu Ścianka lamelowa WOODWALL/  
Technical Data Sheet of the WOODWALL lamella wall**

KTW/D/16/2025  
Updated on: 10/2025  
Prepared by: Product Implementation Specialist

**EN**

<b>General characteristics of the products</b>	WOODWALL spatial walls consist of slats made of MDF material. They are coated with paper veneer (in various colors) using hot-melt adhesive. The whole thing is assembled with screws (self-assembly by the customer).
<b>Dimensions</b>	Height: 2750mm Width: 580mm Depth: 65mm Cross-section of the strips: 65x19mm
<b>Colors</b>	Available colors: Saragossa oak, black Please note: Due to material and technological reasons, differences in shades between individual production batches and within a single product are possible.
<b>Material composition</b>	1. MDF strips 2. Paper veneer 3. Screws and other accessories
<b>Purpose and scope of application</b>	WOODWALL spatial walls are intended for installation inside houses. They are intended to divide space and for decorative purposes. They can be mounted individually or connected together.
<b>Packaging method</b>	The panels are packed in cardboard boxes and include assembly instructions.
<b>Storage and transportation</b>	Products should be stored and transported in their original manufacturer's packaging, under cover. Store only in a dry place and protect from moisture. Please ensure that the walls are transported and stored in a horizontal position, as this may cause permanent deformation. Avoid cleaning with chemicals. Avoid moisture and heat sources. Each package should contain information providing at least the following data: - name and address of the manufacturer, - trade name, - number of pieces in the package, - graphic description of the assembly.
<b>Assembly instructions</b>	The entire assembly process is presented in the user manual. Note: When installing on non-permanent surfaces (lightweight wall construction, suspended ceilings, etc.), ensure that the installation method is appropriately selected to ensure a stable and safe connection of the wall to the permanent structural elements of the building. Note: If renovating a room where a wall is installed, it must be properly secured. Standard masking tape should be used for this purpose, but it should be removed no later than 24 hours after application.
<b>Security</b>	This product is not a toy and should be assembled by adults. Use of the product by children or vulnerable individuals outside of its intended use may pose a risk to their health or life, and the child's guardian or parent is solely responsible for such action. General occupational health and safety regulations must be observed during assembly and use. Keep the product away from heat sources.
<b>Terms of Use</b>	Use the panels as intended at a maximum temperature of 50°C and a maximum relative air humidity of 60%.
<b>Impact of the product on other products</b>	Not applicable
<b>Impact of other products on the product</b>	Do not use chemicals for cleaning. Keep away from sources of fire and heat.

*This product data sheet replaces previous versions.*