

VICTORIA+



Abalone

V10012+



Manyville Brown

V10013+



Davenport Tan

V10009+



Adobe Dust

V10007+



Cedar Key

V10005+



Arizona Tan

V10002+



Morning Sunshine

V10003+



Wild Orchid

V10018+



Sherwood Green

V10021+




Clearspring Green

V10022+



Blue Jean

V10015+



Twilight Blue

V10019+



Metallic Silver

V10011+



Silver Marlin

V10025+



Whale Gray


V10027+



Black Jack


V10030+

NAIVETE




White

N20021



Beige

N20022




Yellow

N20029




Orange

N20030




Light Grey

N20026



Light Green

N20031



Light Blue

N20035




Red

N20032



Dark Grey

N20027



Dark Green

N20033



Dark Blue

N20036



Black

N20046




	VICTORIA+	NAIVETE
Total Thickness EN 428	2.0mm	
Roll Width EN 426	2m	
Roll Length EN 427	20m ^[1]	
Surface Treatment	FirmTech2.0 ^[2]	PUR
Weight EN 430	2850g/sq.m.	3150g/sq.m.
Classification EN 685	Commercial 34 / Industrial 43	
Abrasion Group EN 660	T	T
Fire Rating EN 13501	B _s -s1	
Slip Resistance DIN 51130	R9	
Dimension Stability EN 434	≤0.2% ^[3]	
Residual Indentation EN 433	0.01mm ^[4]	
Formaldehyde Emission EN 717-1	E1	
Flexibility EN 435	No crack	
Thermal Conductivity EN 14041	Approx. 0.01m ² K/W	
Static Electrical Propensity EN 1815	< 2kV	
Color Fastness EN ISO 105-B02	≥6	
Castor Chair Test EN 425	Suitable	
Sound Absorption EN ISO 717/2	Approx. 4dB	
Stain and Chemical Resistance EN 423	Excellent	Great
Bacteria Resistance ^[5] ASTM G21-13 & E2018-07	Excellent	Great
TVOC ISO 16000	<10µg/m ³	
PCP EN 14041 Annex B	ND	
Cleanroom Test ASTM F24-51	Class A	
Ease of Decontamination ISO 8690	Good	
Colors	16	12

FirmTech

Cooperate with specialized laboratories, we have developed unique new surface reinforcement technology. With the addition of high-molecular polymer, flooring anti-scratch performance is much more superior to common standard PUR reinforcement through UV coating equipment. This new technology can better deal with the damages to flooring caused by high-heeled shoes, sickbed wheels and other sharp objects in daily use.

FirmTech also includes OHST mildew-proof and anti-microbial technology. More information, please refer to OHST introduction.

These photos are based on tests we did in our lab, use keys scratch the flooring surface with same force.



Decostar® has a policy of continuous product and product data improvement, it reserves the right to change design and specifications without notice. For the latest Technical Data Sheet, please kindly check www.decostar.gr

[1] The length of standard roll is 20m, there may have short rolls come out from production, the qualified length between 10m and 19m.

[2] FirmTech2.0 is consist of FirmTech, OHST and CleanCare.

[3] Test standard required value ≤ 0.4%, best measured value 0.2%. For information, not binding.

[4] Test standard required value ≤ 0.1mm, best measured value 0.01mm. For information, not binding.

[5] Test includes *Aspergillus niger* ATCC 9642, *Penicillium pinophilum* ATCC 11797, *Aureobasidium pullulans* ATCC 15233, *Chaetomium Globosum* ATCC 6205, *Trichoderma virens* ATCC 9645, *Staphylococcus aureus* ATCC 6538, *Klebsiella pneumoniae* ATCC 4352 and *Pseudomonas aeruginosa* ATCC 9027.

HOMOGENEOUS MASTER

DECOSTAR
DESIGN FLOORING



MASTER SERIES

VICTORIA · NAIVETE

DECOSTAR S.A.
187 – 189 Dimokratias Av. Acharnes Athens
www.decostar.gr