

Continental PC

Manufacturing process	Tufted	ISO 2424
Gauge	5/32" Cutpile	
Pile yarn composition	100% PA6	ISO 2424
Primary backing	Non Woven	
Backing	PC	
Width	90 cm, 100 cm, 200 cm, cm	
Pile weight	520 g/m ²	
Total weight	2787 g/m ²	+/- 10% ISO 8543
Pile height	3.5 mm	ISO 1765
Total height	6.0 mm	+/- 10% ISO 1765
Number of tufts	15470	
Overall use class	Commercial 31, Areas with low or intermittent use	EN 1307
Luxury class	LC2	EN 1307
Castor chair suitability	No	EN 985
Stair suitability	Yes, permanent use	EN 1307
Colour fastness to light	≥ 5	ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4	ISO 105-X12
Colour fastness to water	≥ 4	ISO 105-E01
Colour fastness to soiling	≥ 3,5	EN 1269
Electrostatic charging	< 2kV	ISO 6356
Vertical resistance	< 1,0x10 ⁸ Ω	ISO 10965
Horizontal resistance	< 1,0x10 ⁸ Ω	ISO 10965
Slip resistance	> 0,3 Machine direction > 0,3 Crossdirection	EN 13893 EN 13893
Flammability	Cfl,s1	EN 13501-1
AbZ Nr.	Z-156.601-1165	

Floorsymbols



Certificates

Vebe PA6 / 1145 / PVC



Vebe Floorcoverings b.v. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system (according ISO 9001). The tests have been carried out according to the prescribed standards.