

TECHNICAL SPECIFICATIONS

Standards	ISO/DIS 19322.2:2016 EN649	Heterogeneous PVC
Dimensions		1230 x 192 mm (planks) 620 x 315 mm (tiles)
Total Thickness	ISO 24346	2.5 mm
Wear Layer Thickness	ISO 24340	0.55 mm
Quanty per carton		16 planks / 3.78 m ² 20 tiles / 3.91 m ²
Surface treatment		PU-coating
Bevelled Edge		Yes
Classification	ISO 10874 Commercial ISO 10874 Domestic EN 685 Commercial EN 685 Domestic	33 : Heavy Commercial 23 : Heavy Domestic
Inflammability	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	B _n -s1
Staining Resistance	EN ISO 26987:2012	Class 0
Colour Fastness	EN ISO 105-B02	Grade 6
Fungi Resistance	ISO 846	Growth intensity 0
Indentation - Residual	EN 433	< 0.1 mm
Castor Chair	ISO 4918 EN 425:2002	Pass
Formaldehyde emission	EN 14041:2004	Class E1
Slip resistance	EN 13893 DIN 51130	DS R10
Electrostatic Behaviour	EN1815	Pass
Reach	EC N° 1907/2006	Pass
VOC Emission	French VOC regulation	A+
Emission & Contraction rate	Europe standard ISO 23999:2021	< 0.25%
Density		1950 - 2000 kg/m ³
Weight		4.9 kgs/m ²

Certifications

