



DECLARATION OF PERFORMANCE

DOP QL0502

1. Unique identification code of the product-type:

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Quick-Step Impressive Ultra / Impressive /
Majestic / Waterproof surface flooring /
Impressive Patterns /
Signature/Perspective Nature

Laminate floor coverings following EN13329 7-12 mm

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Unilin, division Flooring, Ooigemstraat 3 - B-8710 Wielsbeke, Belgium

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

IHD / Wood.be / Eurofins

not applicable






Notified Body

certificate of constancy of performance

7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire		EN 14041:2018
Content of Dangerous Substances		
Emission of HCHO		
Emission of VOC without HCHO	TVOC < 0,5mg/m ³	
Slip resistance		
Water-tightness	NPD	
Electrical behavior (antistatic)		
Thermal conductivity [W/mK]	Th res (m2K/W) = 0,055 (8); 0,059 (9); 0,061 (9.5); 0,072 (12)	

9. The performance of the product identified in points 1 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Jasper De Jaeger, technical services manager

(name and function)

Wielsbeke, 10/04/2019

(place and date of issue)

(signature)